



Eye and Eye/Face Washes



Wall-mount eye and eye/face washes include 10" diameter impact-resistant yellow plastic bowl or corrosion-resistant stainless steel bowl. Wall bracket is heavy-gauge aluminum with three clearance holes for wall mounting. Exposed pipes and wall bracket are protected with Bradtec™ safety yellow polyurethane coating to protect unit from corrosion. Units activate by a highly visible plastic push handle and ½" IPS chrome-plated brass stay-open ball valve. Twin sprayheads include a flow control and pop-off dust covers. All units include safety sign and inspection tag. Water supply: ½" IPS (female). Meets ANSI Z358.1-1998 Standards. SEI Certified.

Bradley Part No.	Type/Bowl	Unit of Measure	Wgt. (lbs.)
S19-220	Eyewash/Plastic	1	6.0
S19-220B	Eyewash/Stainless	1	7.0
S19-220FW	Eye/Face Wash/Plastic	1	7.0
S19-220T	Eye/Face Wash/Stainless	1	7.0



Eye/Face Wash with Dust Cover



Wall-mount eye/face wash includes 10" diameter stainless steel corrosion-resistant bowl. Hinged stainless steel dust cover keeps dirt and other contaminants out of the eyewash bowl when not in use. Dust cover pops open when highly visible stainless steel push handle is activated. Handle operates ½" IPS chrome-plated brass stay-open ball valve. Eye/face wash includes twin ABS plastic sprayheads with a flow control. Eyewash includes a safety sign and inspection tag. Water supply: ½" IPS (female). Meets ANSI Z358.1-1998 Standards. SEI Certified.

Bradley Part No.	Type/Bowl	Unit of Measure	Wgt. (lbs.)
S19-220DCFW	Eye/face Wash/Stainless	1	10.0



Retrofit Plastic Dust Cover



Plastic hinged dust cover retrofits onto Bradley 10" diameter plastic eye wash bowl to provide maximum protection from dust or other contaminants from getting in the eye wash bowl and clogging sprayheads and/or drain. Retrofit assembles in 4 easy steps. Simply remove the eye wash handle, drill holes, attach the cover and then reattach the handle.

Bradley Part No.	Type/Bowl	Unit of Measure	Wgt. (lbs.)
S45-1964	Retrofit Plastic Dust Cover	1	5.0



Pedestal-Mount Eye and Eye/Face Washes



Pedestal-mount eye and eye/face washes include 10" diameter impact-resistant yellow plastic bowl or corrosion-resistant stainless steel bowl. Units activate by a highly visible plastic push handle and ½" IPS chrome-plated brass stay-open ball valve. Twin sprayheads include a flow control and pop-off dust covers. Galvanized steel pipe is 1¼" and protected with Bradtec™ safety yellow polyurethane coating to help protect from corrosion. All units include safety sign and inspection tag. Water supply: ½" IPS (female). Waste: 1¼" IPS (female). Meets ANSI Z358.1-1998 Standards. SEI Certified.

Bradley Part No.	Type/Bowl	Unit of Measure	Wgt. (lbs.)
S19-210	Eye Wash/Plastic	1	15.0
S19-210B	Eye Wash/Stainless	1	16.0
S19-210FW	Eye/Face Wash/Plastic	1	17.0
S19-210Y	Eye/Face Wash/Stainless	1	20.0



Swing-Activated Eye and Eye/Face Washes



Swing-activated eye and eye/face Washes mount to a counter or a wall next to a sink (swing-over units can be counter mounted only). 90° swivel activates eyewash over sink to begin flow of water to cleanse eyes. Spent water drains into the sink while in use. Eyewash stows neatly to side of sink when not in use to save space. Twin sprayheads include a flow control and pop-off dust covers. All units include a safety sign and inspection tag. Water supply: ½" IPS (female). Meets ANSI Z358.1-1998 Standards. SEI Certified.



Bradley Part No.	Type/Bowl	Unit of Measure	Wgt. (lbs.)
S19-270C	Eyewash (Swing Over)	1	5.0
S19-270E	Eye/Face Wash (Swing Over)	1	5.0
S19-270HD	Deck-Mounted Eyewash (Swing Down)	1	5.0
S19-270HW	Wall-Mounted Eyewash (Swing Down)	1	5.0
S19-270JD	Deck-Mounted Eye/Face Wash (Swing Down)	1	5.0
S19-270JW	Deck-Mounted Eye/Face Wash (Swing Down)	1	5.0



Faucet-Mount Eyewash

Faucet-mount eyewash mounts to standard or gooseneck type faucets. Simply remove existing faucet aerator and replace with faucet mount eyewash aerator adapter. Adapter on unit is 55/64" x 27 thread (female) but includes two additional adapters to fit most faucets, 13/16" x 27 thread (male) and 15/16" x 27 thread (male). Twin sprayheads include a flow control and pop-off dust covers. Unit activates by a actuator pin on adapter. When pin is in closed position, faucet can be used for normal operation. Eyewash includes a safety sign and inspection tag. Meets ANSI Z358.1-1998 Standards. SEI Certified.



Bradley Part No.	Type/Bowl	Unit of Measure	Wgt. (lbs.)
S19-200B	Faucet-Mount	1	1.0



On-Site® Gravity-Fed Eyewash and Transport Cart

- Now fully transportable
- Relocate to Point-of-Need even when assembled and filled on maintenance vehicles, hand carts, or Bradley Waste Cart.



Gravity-fed eyewash mounts to a wall or can be placed on a counter-top or other solid surface. Eyewash is light weight – only 7 gallons or 60 lbs. full and can be easily transported from one location to another. Transparent polycarbonate tank allows you to see at a glance when it is time to clean or refill unit. Eyewash activates water flow when hinged eyewash tray is pulled down. Safety sign included. Sprayheads provide a continuous flow of water for 15 minutes at .4 gpm. Meets ANSI Z358.1-1998 Standards. SEI Certified.

Transport Cart includes rigid casters in front and locking swivel casters in back for easy transportation of Gravity-fed unit. Waste collection tank is 56 gallons with 1/2" petcock at bottom for easy draining of waste over a floor drain.

Bradley Part No.	Type/Bowl	Unit of Measure	Wgt. (lbs.)
S19-921	Gravity-Fed Ey Wash	1	23.0
S19-921H	Gravity-Fed Eyewash with Heater Jacket	1	25.0
S19-865	Water Preservative	1	3.0
S19-899	Refill Kit	1	2.0
S19-399	Transport Cart	1	28.0



Drench Hose Sprays

Hand-held hose sprays are available with single spray head or twin sprayhead assemblies. Sprayheads are ABS plastic and include a flow control and pop-off dust covers. Valve is chrome-plated and stays open when handle is squeezed. Yellow 8' hose is rated at 250 PSI burst strength. Counter-mount units include a under the counter hose guide and wall mount units include a wall hanging bracket. Water supply: 3/8" IPS (male). Meet ANSI Z358.1-1998 Standards as supplements to eyewash and shower products only.



Bradley Part No.	Type/Bowl	Unit of Measure	Wgt. (lbs.)
S19-460	Single Head, Counter	1	5.0
S19-430A	Single Head, Wall	1	5.0
S19-460EFW	Twin Head, Counter	1	6.0
S19-430EFW	Twin Head, Wall	1	5.0



Portable Pressurized Eyewashes

Stainless steel pressure tanks include tire filler valve with 0-100 PSI air gauge, pressure relief valve to prevent over pressurization and built in carry handles for easy transportation. Eyewash assembly includes twin eyewash heads with a flow control and pop-off dust covers. Eyewash activates by a large stainless steel push handle with stay-open ball valve. Supplemental hose spray for face and body rinse has 8' yellow hose with hand-held squeeze valve. Eyewashes maintain minimum 15 minute water flow and drench hose maintains 3 1/2 minute water flow. Meets ANSI Z358.1-1998 Standards. SEI Certified.



Bradley Part No.	Type/Bowl	Unit of Measure	Wgt. (lbs.)
S19-690	10-Gallon	1	30.0
S19-690H	10-Gallon with Heater Jacket	1	31.0
S19-788	15-Gallon	1	35.0
S19-788H	15-Gallon with Heater Jacket	1	36.0
S19-690A	S.S. Transport Cart	1	12.0



Combination Drench Showers

Showers include either yellow impact-resistant plastic or corrosion-resistant stainless steel 10" diameter showerheads that activate by a pull rod and 1" IPS chrome-plated stay-open ball valve. Eye and eye/face washes include twin sprayheads with a flow control and pop-off dust covers with either yellow impact-resistant plastic or corrosion-resistant stainless steel 10" diameter bowls. Eye and eye/face washes activate by highly visible push handle and 1/2" IPS chrome-plated stay-open ball valve. Some units can be hand or foot control operated. All units include 1 1/4" galvanized pipe and floor flange and is protected by a yellow polyurethane coating to withstand harsh/corrosive environments. Safety sign and inspection tag is also included. Water supply: 1 1/4" IPS (female). Waste: 1 1/4" IPS (female). Meets ANSI Z358.1-1998 Standards. SEI Certified.



Bradley Part No.	Shower Head	Bowl	Unit of Measure	Wgt. (lbs.)
S19-310	Plastic	Plastic, Eyewash	1	41.0
*S19-310UU	Stainless	Stainless, Eyewash	1	44.0
*S19-310LL	Plastic	Stainless, Eyewash	1	42.0
S19-310FW	Plastic	Plastic, Eye/Face Wash	1	41.0
*S19-310AC	Plastic	Stainless, Eye/Face Wash	1	42.0

*Indicates Hand or Foot Operated



Corrosion-Resistant Combination Drench Showers

PVC combination drench shower with eye/face wash includes yellow plastic shower head activated by a pull rod and 1" IPS chrome-plated stay-open ball valve. Eye/face wash includes plastic bowl with twin plastic sprayheads. Eye/face wash activates by a plastic push handle and 1/2" IPS chrome-plated brass stay-open ball valve. Fittings for PVC unit are all stainless steel. 2" schedule 80 PVC pipe and floor flange withstands highly corrosive environments including chlorine. Type 304 all Stainless steel combination drench shower with eye/face includes all stainless steel showerhead operated by a pull rod with 1" IPS stainless steel stay-open ball valve. Stainless steel eyewash bowl with face spray ring is operated by a stainless push handle and stainless steel 1/2" IPS stay-open ball valve. 1 1/4" all stainless pipe and floor flange withstands highly corrosive environments. Units include a safety sign and inspection tag. Water supply/waste: 2" IPS (female for PVC Unit), 1 1/4" (female for stainless steel unit). Meets ANSI Z358.1-1998 Standards. SEI Certified.



Bradley Part No.	Type/Bowl	Unit of Measure	Wgt. (lbs.)
S19-310PVC	PVC Comb. Eye/Face Wash	1	35.0
S19-310SS	Stainless Steel Comb. Eye/Face Wash	1	50.0



Combination Barrier-Free Drench Shower

Combination drench shower and eye/face wash includes yellow plastic showerhead activated by a pull rod and 1" IPS chrome-plated stay-open ball valve. Eye/face wash includes stainless steel bowl with twin sprayheads and face spray ring assembly. Eyewash activates by a stainless steel push handle and 1/2" IPS chrome-plated brass stay-open ball valve. 1 1/4" galvanized pipe and floor flange is protected by a yellow polyurethane coating for corrosion resistance. Shower design allows you to meet accessibility codes by assuring proper placement of shower and eyewash components - shower pull rod is longer and eyewash bowl is lower and extends further from the wall to provide easy access for a wheelchair. Unit includes a safety sign and inspection tag. Water supply: 1 1/4" IPS (female). Waste: 1 1/4" IPS (female). Meets ANSI Z358.1-1998 Standards. SEI Certified.



Bradley Part No.	Type/Bowl	Unit of Measure	Wgt. (lbs.)
S19-310BF	Comb. Barrier-Free	1	48.0



Horizontal and Vertical Supply Drench Showers

Designed for wall (horizontal) or ceiling (vertical) mounting. Showers include either 10" diameter impact-resistant plastic or corrosion-resistant stainless steel showerheads. Flush mount shower includes a stainless steel integral shower head flange to mount even with ceiling to conceal pipe and fittings. Showers activate with pull rod and 1" IPS chrome-plated brass stay-open ball valve. Pipe is 1" galvanized steel protected with a yellow polyurethane coating to prevent corrosion. Water supply: 1" IPS (female) All units include safety sign and inspection tag. Meet ANSI Z358.1-1998 Standards. SEI Certified.



Bradley Part No.	Type/Bowl	Unit of Measure	Wgt. (lbs.)
S19-120	Horizontal, Plastic	1	7.0
S19-120A	Horizontal, Stainless	1	8.0
S19-130	Vertical, Plastic	1	5.0
S19-130A	Vertical, Stainless	1	6.0
S19-120FM	Horizontal, Flush Mount	1	8.0



Thermostatic Mixing Valves

Thermostatic Mixing Valves blend hot and cold water to a comfortable flushing temperature. ANSI Standards require tepid water to assure that eyewash and drench shower users are not subject to scalding or freezing water temperatures. Valves are pre-set at 85° F but can be adjusted to other temperature set points. Valves are available in three options to accommodate various equipment applications: 8 GPM accommodates up to three eyewashes or one eye/face wash, 36 GPM accommodates one combination shower with eyewash, one drench shower or multiple eyewashes, 67 GPM accommodates up to two combination showers with eyewashes, three drench showers or multiple eyewashes. **Note:** Bradley Fixtures Corporation recommends the use of the S19-866 20 GPM showerhead flow control when sizing drench showers and combination drench showers with eye washes.



Bradley Part No.	Type/Bowl	Unit of Measure	Wgt. (lbs.)
S19-2000	8 GPM	1	5.0
S19-2100	36 GPM	1	20.0
S19-2200	67 GPM	1	30.0



Heat Trace Combination Drench Shower with Eye/Face Wash

Heat trace combination drench shower with eye/face wash is wrapped in heat-trace cable surrounded by insulation and enclosed with 3/4" polyethylene yellow removable shell. Unit includes yellow plastic shower head activated by a pull rod and 1" IPS chrome-plated brass stay-open ball valve. Eye/face wash includes ABC plastic twin sprayheads and activates by a stainless steel push handle and 1/2" IPS chrome-plated brass stay-open ball valve. Shower design allows this unit to be installed in up to -50° F freezing conditions. Freeze protection valve ensures continual flow of water when internal temperatures drop below 35° F. Valve closes at 45° F. Temperature control thermostat opens at 64° F and closes at 54° F. Junction box is 4-hub aluminum and accepts 3/4" IPS conduit. Unit requires 120V AC or 240V AC service voltage. Unit includes a safety sign and inspection tag. Water supply (must specify T(top) or B(bottom): 1 1/4" IPS (female). Waste: 1 1/4" IPS (female). Meets ANSI Z358.1-1998 Standards, rated Class I Division II Groups B,C,D. SEI Certified. **Options include:** Shower Alarm, Indicator Light, Drench Hose and Scald Protection Valve.



Bradley Part No.	Type/Bowl	Unit of Measure	Wgt. (lbs.)
S19-300T/B	Heat Trace Combination Unit	1	110.00